


## Roller chain 06B-1 Straight side plates - ecoplus - 150m reel



Part no.: 81012502

Packaging Unit: 5m

Brand: ecoplus

Model: Straight side plates

**ecoplus®**

## Technical data

ROLLER CHAIN	06B
Pitch p (mm)	9,525
Width between inner plates b1 min. (mm)	5,72
Roller diameter d1 max. (mm)	6,35
Pin diameter d2 max. (mm)	3,28
Pin length b4 max. (mm)	13,5
Max. add. length of connecting link b7 max. (mm)	3,3
Total width inner link b2 max. (mm)	8,53
Plate thickness Ti/To (mm)	1,30/1,30
Height inner plate h2 max. (mm) (JWIS: g)	8,26
Min. tensile strength ISO/DIN FU (kN)	8,9
Weight per meter (kg)	0,41
Bearing surface f (cm <sup>2</sup> )	0,28

## Product Information

ecoplus is the iwis economy brand for light-duty applications with low performance requirements. All ecoplus roller chains are intended for universal use and are therefore lubricated with only one light corrosion protection oil.

### Ecoplus Highlights

- All ecoplus chains are pre-stretched with >30% breaking force following assembly.
- ecoplus standard chains possess especially high breaking strength thanks to special ecoplus pins with high core hardness.

- Case hardened bushes and rollers
- Links plates are heat-treated and black oxidised
- The initial lubrication ECO-1 is an anti-corrosion mineral oil-based lubricant

## Applications

- Mechanical engineering and systems construction
- Conveyor technology

**REQUEST DIRECTLY ONLINE NOW**

<https://www.iwis.com/en-en/products-services/roller-chain-06b-1-straight-side-plates-ecoplus-150m-reel~p1010365>

## Useful information

### **CALCULATION PROGRAM**

InduKet: the Chain Drive  
Calculation Program for  
Engineers.

[iwis.com/chaincalc](https://www.iwis.com/chaincalc)

### **CHAIN CALCULATION**

The right drive solution for your  
challenge.

[chaindrive@iwis.com](mailto:chaindrive@iwis.com)

### **SERVICES**

ChainFinder, CAD data, iwis  
Chain Handbook and more.

[iwis.com/services](https://www.iwis.com/services)