



Conveyor chain MR 160 Scraper conveyor chain MR series - ELITE


Part no.: I2444c60d6830

Brand: ELITE

Model: Scraper conveyor chain MR

series





Technical data

ROLLER CHAIN	MR 160
Pitch p (mm)	160
Width between inner plates b1 min. (mm)	37
Pin diameter d2 max. (mm)	18

www.iwis.com

Product data



Bush diameter d3 max. (mm)	25
Plate thickness Ti/To (mm)	7
Height inner plate h2 max. (mm) (JWIS: g)	50
Pin to top of scraper h4 (mm)	40
Min. tensile strength ISO/DIN FU (kN)	160

Product Information

In the context of the ELITE conveyor chain range, iwis supplies a wide variety of chains according to standards DIN 8165 and DIN 8167, as well as models manufactured according to British Standard with dimensions in inches, and highly diverse special versions. Bush conveyor chains are often used for conveying tasks involving long transport distances at relatively low speeds.

ELITE highlights

- · Pins usually made of heat-treated alloy steel, induction-hardened or tempered
- Bushes made from seamless precision steel tube, case-hardened
- · Link plates made of high-strength tempered steel
- · Rollers (where present) made of case-hardened steel, case-hardened

Applications

- · Wood processing industry
- · Steelmaking industry
- · Automotive industry
- · Bulk goods transport
- · Environmental technology, Recycling

REQUEST DIRECTLY ONLINE NOW

https://www.iwis.com/en-en/products-services/conveyor-chain-mr-160-scraper-conveyor-chain-mr-series-elite~p4573

Useful information

www.iwis.com 2



CALCULATION PROGRAM

InduKet: the Chain Drive Calculation Program for Engineers.

iwis.com/chaincalc

CHAIN CALCULATION

The right drive solution for your challenge.

chaindrive@iwis.com

SERVICES

ChainFinder, CAD data, iwis Chain Handbook and more.

iwis.com/services

www.iwis.com 3