




Conveyor chain FVR 90 Scraper conveyor chain FVR series - ELITE

Part no.: lcb6cb6ef3d9a

Brand: ELITE

Model: Scraper conveyor chain FVR
series



Technical data

ROLLER CHAIN	FVR 90
Pitch p (mm)	125
Width between inner plates b_1 min. (mm)	25
Pin diameter d_2 max. (mm)	14

Bush diameter d3 max. (mm)	20
Plate thickness Ti/To (mm)	5
Height inner plate h2 max. (mm) (JWIS: g)	35
Pin to top of scraper h4 (mm)	30
Min. tensile strength ISO/DIN FU (kN)	90

Product Information

In the context of the ELITE conveyor chain range, iwis supplies a wide variety of chains according to standards DIN 8165 and DIN 8167, as well as models manufactured according to British Standard with dimensions in inches, and highly diverse special versions. Bush conveyor chains are often used for conveying tasks involving long transport distances at relatively low speeds.

ELITE highlights

- Pins usually made of heat-treated alloy steel, induction-hardened or tempered
- Bushes made from seamless precision steel tube, case-hardened
- Link plates made of high-strength tempered steel
- Rollers (where present) made of case-hardened steel, case-hardened

Applications

- Wood processing industry
- Steelmaking industry
- Automotive industry
- Bulk goods transport
- Environmental technology, Recycling



REQUEST DIRECTLY ONLINE NOW

<https://www.iwis.com/en-en/products-services/conveyor-chain-fvr-90-scraper-conveyor-chain-fvr-series-elite~p4592>

Useful information



CALCULATION PROGRAM

InduKet: the Chain Drive
Calculation Program for
Engineers.

[iwis.com/chaincalc](https://www.iwis.com/chaincalc)



CHAIN CALCULATION

The right drive solution for your
challenge.

chaindrive@iwis.com



SERVICES

ChainFinder, CAD data, iwis
Chain Handbook and more.

[iwis.com/services](https://www.iwis.com/services)